



Seitenkanalgebläse Europa



Model	Watt	Freq	Volt	Fase	m ³ /h	Druck max.Anschl.
40-01	200	50Hz	220	1	40	70 mBar 1"
40-02	230	60Hz	220	1	55	70 mBar 1"
40-03	200	50Hz	380	3	40	70 mBar 1"
40-04	230	60Hz	380	3	55	70 mBar 1"
55-01	250	50Hz	220	1	55	80 mBar 1"
55-02	280	60Hz	220	1	60	80 mBar 1"
55-03	250	50Hz	380	3	55	80 mBar 1"
55-04	280	60Hz	380	3	60	80 mBar 1"
80-01	400	50Hz	220	1	80	130 mBar 1¼"
80-02	500	60Hz	220	1	98	170 mBar 1¼"
80-03	400	50Hz	380	3	80	130 mBar 1¼"
80-04	500	60Hz	380	3	98	170 mBar 1¼"
150-01	850	50Hz	220	1	145	160 mBar 1½"
150-02	950	60Hz	220	1	175	160 mBar 1½"
150-03	850	50Hz	380	3	145	160 mBar 1½"
150-04	950	60Hz	380	3	175	160 mBar 1½"



Airblowers SKG

Model	Watt	Freq	Volt	Fase	m ³ /h	Druck max.Anschl.
151-01	1.300	50Hz	220	1	145	200 mBar 1½"
151-02	1.500	60Hz	220	1	175	230 mBar 1½"
151-03	1.300	50Hz	380	3	145	200 mBar 1½"
151-04	1.500	60Hz	380	3	175	230 mBar 1½"
152-02	1.600	50Hz	380	3	150	300 mBar 1½"
225-01	1.300	50	220	1	210	170 mBar 2"
225-02	1.500	60	220	1	255	140 mBar 2"
225-03	1.300	50	380	3	210	170 mBar 2"
225-04	1.500	60	380	3	255	140 mBar 2"
226-01	1.500	50	220	1	210	220 mBar 2"
226-02	1.750	60	220	1	255	220 mBar 2"
226-03	1.500	50	380	3	210	220 mBar 2"
226-04	1.750	60	380	3	255	220 mBar 2"
320-01	3.000	50	380	3	318	280 mBar 2"

Empfohlenes Zubehör nicht im Lieferumfang einbegriffen.

Luftfilter	Anschl.	Flow max.
LuFi 01		1¼"100 m3
LuFi 02		1½"200 m3
LuFi 03		2"300 m3

Druckreduzierventil

Dru 01	1¼"0-300 mBar
Dru 02	1¼"0-600 mBar

Lärmreduzierventil

Gel 01	1¼"
Gel 02	1½"
Gel 03	2"

Seitenkanalgebläse bis 2.000 m3 Luft pro Stunde und 1.000 mBar Druck lieferbar.